

## **Beaverswood®**

### Anti-Slip Tape Rolls

Our **anti-slip tape** is manufactured through a unique process ensuring it's one of the most effective anti-slip surfaces available. The tape material is a thick carrier impregnated with diamond-hard aluminium oxide, making it hard-wearing as well as improving foot traction to prevent slips. The backing is coated in a heavy layer of permanent pressure-sensitive adhesive which is water-resistant and extremely durable.



## **Features and Benefits**

- The tape material is impregnated with diamond-hard aluminium oxide, creating a perfect texture to enhance foot traction and prevent slipping.
- Tough and durable, withstanding most chemicals.
- High levels of grip (coefficient of friction).
- Peel-resistant and water-resistant to withstand heavy footfall in differing weather conditions.
- Easy to cut to size and install.
- Simply peel off the backing and stick the tape down on the desired surface (ensuring the surface is clean, flat, and dry during installation).
- Rolls of tape various widths and colours.
- 18.3 M rolls.



<b>Material</b>	0.1mm PVC back carrier with abrasive aluminium oxide secured by polymer resin
<b>Widths</b>	25 mm / 50 mm / 100 mm / 150 mm
<b>Length</b>	18.3 M
<b>Adhesive</b>	Pressure sensitive solvent acrylic based
<b>Temperature range</b>	-40°C to 80°C
<b>Adhesion to steel</b>	Over 1500 g/25.4 mm <sup>2</sup>
<b>Tensile strength</b>	Over 6 kg/25 mm <sup>2</sup>
<b>Tear resistance</b>	5600 g +/- 200 g
<b>Peel adhesion</b>	23.5N/25 mm
<b>Elongation at break</b>	Over 25%
<b>Resistance to water</b>	10 months
<b>Resistance to chemicals</b>	8 months
<b>Resistance to oil</b>	Excellent
<b>Expected life</b>	12 to 36 months
<b>Dry surface pendulum</b>	102 TRL
<b>Wet surface pendulum</b>	71 TRL
<b>DIN 51130</b>	R13
<b>DIN 51130</b>	Inclination 30°C
<b>DIN 51130</b>	High traction